

you can
Canon

LaserBase MF3240



Easy to use, efficient Laser All-in-One with fax functionality.

The LaserBase MF3240 is part of the Canon LaserBase range.

The whole LaserBase range consists of: MF8180C, MF6580PL, MF6560PL, MF6550, MF6540PL, MF6530, MF5770, MF5740, MF5730, **MF3240** and MF3220

Embargo: 14th April 2006
Sales Start Date: 1st June 2006
Target Market: small & medium SOHO

Key Features

- Affordable Laser All-in-One: printer, fax, copier, colour scanner
- Quick first print/copy from standby mode, under 11 seconds
- 20 pages/copies per minute, 1200 x 600dpi printing (enhanced)
- Super G3 fax modem, 3 seconds per page* transmission
- 256-page* fax memory, UHQ technology with 256 greyscales
- Colour scanner: 600 x 1200dpi, save to PDF functionality
- Flexible paper supply, 250-sheet paper cassette
- All-in-One Cartridge: maintenance free, continuous high quality
- Network print/PC fax/scan with optional Axis 1650 Print Server
- USB2.0 Hi-Speed interface

* based on ITU-T Standard Chart No. 1

Product Name	Mercury Code	EAN Code	Recommended Retail Price
LaserBase MF3240	0989B018AA	8714574973166	£199

What's in the box:

Main unit, All-in-One cartridge EP-27, power cord, telephone line cable, USB cable, starter guide, CD-ROM for driver, CD-ROM user manual, fax destination labels, warranty card

New Consumables*	Mercury Code	EAN Code	Recommended Retail Price
Cartridge EP-27	8489A002AA	4960999201719	£65.99

* For full list of media types see technical specifications

you can
Canon

LaserBase MF3240



Technical Specifications

TYPE	Machine type Available functions Paper scanning type	Laser flatbed All-in-One Print, Scan, Copy and Fax Flatbed
PRINTER FUNCTIONS	Printing method Print speed Print resolution Printer Memory Cartridges Yield Smoothing (dpi) Paper capacity Paper Size Maximum printing width Toner saver mode	Mono laser beam printing 20 pages per minute 600 x 600 dpi 32MB EP-27 Cartridge 2500 pages (Based on ISO/IEC19752) 1200 x 600 dpi 250 sheets A4, LTR, LGL, Envelope (COM10, Monarch, DL, ISO-5) 216mm Yes (Cartridge yield – approx 3125 pages)
FAX FUNCTION	Standalone fax PC fax Transmission speed Modem speed Compression method Fax resolution Image processing system Halftone Memory transmission FAX memory Dual access One touch dials Coded dials Group dial Redial FAX/TEL auto switch Answering machine hook up Remote reception Sequential broadcast Error correction mode(ECM) Memory reception Reports	Yes Yes Approx 3 secs/page at 33.6kbps * 33.6kbps MH, MR, MMR Standard, Fine, Superfine UHQ 256 grey scale Yes 256 pages ¹⁾ Yes 7 100 7 (max. 50 locations) Yes (automatic and manual) Yes Yes Yes Yes (max. 123 locations) Yes Yes (256 pages ¹⁾) Activity Report, TX Result Report, RX Result Report, Memory Data List, Memory Image Print, One-Touch/ Coded/Group Dial List, Users Data List, Lost Report
SCANNER FUNCTIONS	Scanner type Automatic document feeder Scanner resolution Colour scanning depth Greyscale gradation Compatibility Effective scanning width OCR Software bundled Other features	Colour CIS No 600 x 1200dpi 24bit/24bit (in/out) 8bit TWIN, WIA 216mm Yes Dust and scratch removal, Scan to PDF, Scan to Email
COPIER FUNCTIONS	Copy resolution Copy modes Copy speed Multiple copy Zoom ratio First copy output time (FCOT) Other features	600 x 600 dpi Text, Photo, Text & Photo 20 copies per minute Up to 99 copies 50-200% Less than 11 seconds 2-on-1 Copy, First warm up time less than 8 secs

PC INTERFACE AND SOFTWARE	Interface type Software Supported OS PC FAX (TX) PC FAX (RX) Printer drivers Scan drivers Scan to E mail Other features Number of languages (Windows 98/ME/2000/XP) Bundled Software Network option	USB 2.0 Hi-Speed Windows 98/Me/2000/XP Yes No Yes Yes Yes Scan to PDF, Scan to OCR, Scan to Email English, French, German, Italian, Spanish, Dutch, Polish, Russian Presto!PageManager, ScanSoft OmniPage SE (TBC) Yes (AXIS 1650)
GENERAL SPECIFICATIONS	Number of language (LCD message) Dimensions with trays (W x D x H) Dimensions without trays (W x D x H) Installation space including trays (WxD) Weight Power Source Consumption Acoustic Noise Levels	16 languages (English, German, French, Spanish, Italian, Swedish, Norwegian, Dutch, Finnish, Danish, Portuguese, Slovenian, Czech, Hungarian, Russian, Turkish) 449mm x 487mm x 369mm 449mm x 546mm x 369mm 449mm x 462mm Approx. 11.kg AC 200-240V, 50-60Hz Max: Approx. 700w Standby: Less than 8W Energy Save: approx 5W Standby: 30dB(A) max Copy: under 56dB(A) max
SYSTEM REQUIREMENTS	Software Operating System	Windows 98/Me/2000/XP 100MB of available hard disk space (150MB is recommended) 64MB RAM (128MB is recommended) 128MB RAM (256MB is recommended) for USB 2.0 Hi-Speed
OPTIONS	Items	AXIS 1650 Network Print Server

¹⁾ Based on IUT Standard Chart.

All data is based on Canon's standard testing methods.
This leaflet and the specifications of the product have been developed prior to the date of product launch.
Final specifications are subject to change without notice.
™ and ® All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.



Automatic Image Refinement

